

10 YEARS OF SAFE OPERATION AT THE CANADIAN LIGHT SOURCE – A RADIATION SAFETY PERSPECTIVE

Cubbon, G., Chowdhury, P., Street D., Albert, A.

RADSYNCH15

DESY

Hamburg, Germany.

June 4, 2015



Canadian Light Source
Centre canadien de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

The Canadian Light Source



BMFT

BXDX



Canadian
Light
Source

Centre canadien
de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

Outline

- **CLS Facility Description**
- **Radiation Safety Program**
 - Federal Regulations
 - Design
 - Operations
 - Access Control and Interlock
 - Shielding
 - Radiation Monitoring
 - Medical Isotope Program
- **Future**
 - Top-Up Operation
 - Personal Dosimetry Requirements



1999

3.32 Hectares located on
University of Saskatchewan Campus



Saskatoon – the advantage of co location



**University of
Saskatchewan**

**National
Research
Council**

**Agriculture &
Agri-Food
Canada**

**Canadian
Light Source**

Highlights/Firsts

- 1999: Formal funding announcement; Start of construction.
- 2001: Main experimental hall building construction is complete and ready for occupancy. LINAC upgrade commissioning underway.
- 2002: Start of commissioning the booster ring. (The 2.9 GeV electrons produced are the highest energy achieved by any Canadian particle accelerator to date)
- 2003: Start of commissioning the main storage ring.
 - First synchrotron light detected in the Optical Diagnostics Beamline.
- 2004: First x-rays detected in the SGM Beamline.
 - Commissioning of the storage ring is completed.
 - First experimental data recorded on the SGM Beamline.
 - Official Grand Opening.
- 2005: First synchrotron user!!



Electron Gun

- 2 Stories underground
 - Former SAL
- 220 kV Operating Voltage
- 60 mA Average Current
- 1Hz



LINAC

- 6 Section Linac
- 70 or 140 nS pulse
- 250 MeV
- Energy Compression
- Linac-to-Booster (LTB)
 - 70 meters long
 - Up two floors



Booster Ring

- 250 MeV to 2.9GeV
- 10 mA design average operating operating current
 - 3 to 4 mA normal
- 20 dipoles
- 28 quadrupoles
- 2 RF cavities



Storage Ring

- 24 Dipoles
- 12 straight sections
 - 9 available for insertion devices
- Superconducting RF cavity
- 2.9 GeV
- 171 meters diameter





Beamlines

- 14 Operational Beamlines
- 2 diagnostic beamlines
- 7 commissioning or under construction
- Infrared to Hard X-ray



Booster & Storage Rings



Electron
stream



Canadian
Light
Source

Centre canadien
de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

Inside the CLS

CLS Layout

Linac - LTB1

BR1 - BTS1


SR1

Shielding

Operating

Construction

Available



Inside the CLS



Canadian
Light
Source

Centre canadien
de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

CANADIAN REGULATIONS

- Canadian Nuclear Safety Commission (CNSC)
 - Creates regulations
 - Grants licenses for nuclear facilities
 - Oversees compliance
 - Class 1B Licence
 - U mines
 - U Fuel Fabrication
 - Waste Disposal
 - Using or processing $>10^{15}$ Bq other than U fuel
 - > 50 MeV accelerator
- Safety Case
 - Licence Condition Handbook
 - Radiation Protection Program



RPP – Facility Design

- **CLS Regulatory Design Basis**
- CLS Nuclear Energy Worker (NEW) 10 mSv
 - One-year dosimetry period
 - CNSC 50 mSv
- CLS Non-NEW 1 mSv
 - Employees, Users, Contractors
 - One calendar year
 - Member of the public
- Worst case accident dose 1 mSv



RPP – Facility Design

- **CLS Operational Design Considerations**
- Linac
 - 250 MeV
 - 1 Hz
- Booster Ring
 - 2.9 GeV Max
 - 10 mA average current
 - Dose rate in RCA from injection max 80 $\mu\text{Sv/h}$
 - 15 minutes of injection time every 4 hours
- Storage Ring
 - 2.9 GeV Max
 - Dose rate max of 5 $\mu\text{Sv/h}$ in CAZ
 - 500 mA max stored current
- Beamlines
 - 2 $\mu\text{Sv/h}$
 - Bremsstrahlung + Synchrotron (1+1)



Design Philosophy

- 0.5 $\mu\text{Sv/h}$??
- 5 $\mu\text{Sv/h}$ X 2000 h/year = 10 mSv
- (@30 cm from outer wall)
- Build to meet minimum
- Add local shielding where required
- Verify
- ALARA
- Defense in Depth

Current Operation

- 250 mA stored beam in normal mode
 - 1 superconducting cavity installed
- Injection < 10 minutes every 12 hours



Shielding Design

- Initial accelerator shielding based on
 - IAEA 188 (Swanson)
 - H.G. Moe et al

$$H_B(\theta_B) = 0.167 E_o (2^{-\theta_B/\theta_{1/2}}) + 8.33 (10^{-\theta_B/21}) + 0.25 (10^{-\theta_B/110})$$

$$D = 3600 \times P \times \sum_i \left(\frac{H}{r^2} \times e^{\left(\frac{-\rho d}{\lambda_i} \right)} \right)$$

- beamline shielding
 - STAC8, TVdose
 - EGS



Commissioning

- Optimization of Operation and Safety
- Only commissioning team allowed during machine commissioning
- Evenings + Overnights

- LINAC
 - Completed in 2002
- BR1
 - Completed in 2003
- SR1
 - Completed in 2004
- Beamlines
 - Ongoing (neverending?)



COMMISSIONING

- Beamlines
 - Commissioning plan
 - Detailed radiation surveys
 - Primary Enclosure (White beam) vs Optical Enclosure (monochromatic beam)
- Changes to accelerator
 - New components
 - Design changes



Bulk Shielding

Bulk shielding at CLS



Storage Ring Outer Wall



Beamline Enclosure

SHIELDING

- Local Shielding
- Master Shielding Drawing and checklist
- Shielding checks performed prior to start up after extended shutdown
- Personnel Protection vs Machine Protection
- Some Shielding Interlocked





ACIS

- Access Control and Interlock System (Personal Protection System)
- Accelerator, beamlines
- Design
 - Redundant and independent radiation source shut-off systems
 - E Gun
 - Linac, Booster Ring Storage Ring RF
 - Front End Safety shutters
 - Relay based system + Safety rated PLC system
- Testing
 - Commissioning
 - Annual V&V
- Training
 - Provided to staff by HSE
 - Users trained as part beamline specific training



ACIS



RADIOACTIVE MATERIAL

- Sealed Sources – check sources
- Activated material (procedure for storage and release)
- Radioactive samples and beamlines
 - limited to mostly use of low level U tailings to date.



RADIOLOGICAL MONITORING

Personnel Monitoring

- All staff NEW at first
 - Everyone working at CLS assigned a dosimeter
 - Gamma + Neutron
 - Exchanged quarterly
 - EPD for special situations (tours, HRA work, residual survey not complete)
 - Action levels 2.0 mSv for NEW
 - Internal Admin level 0.6 mSv
 - 0.2 mSv for non-NEW

Plan to remove Luxels from Users/Admin staff in future.



Radiological Monitoring





Personal Dosimeter



Electronic Personal Dosimeter


Personal Dosimetry



- Collective doses to all workers low
- Max dose has never exceeded public limit for any worker
- Background issue in 2012 resolved
- 2013 elevated levels due to in transit irradiation of dosimetry shipment
- No personal neutron dose recorded
- > 95% dosimeters with no dose


RADIOLOGICAL MONITORING

- Passive Area Monitoring
 - Luxel- some with Neutrak (CR-39) chip
 - throughout facility (>500 locations)
 - Exchanged quarterly




RADIOLOGICAL MONITORING

- Active Area Radiation Monitoring System (AARMS)
 - Canberra ADM, IP-100, NP-100 (BF_3 , He)
 - 2.5 μSv hourly cumulative dose interlock
 - 50 $\mu\text{Sv/h}$ $\mu\text{Sv/h}$
 - 100 $\mu\text{Sv/h}$ alarm



Active Radiation Monitors



RADIOLOGICAL MONITORING

- Prompt Radiation Surveys
 - Performed regularly on
 - Storage Ring
 - Beamlines
 - Injection vs stored beam
- Residual Radiation Surveys
 - Performed prior to extended shutdowns or when required for special work
 - Machining radioactive material



RADIOLOGICAL MONITORING



Ludlum 2360 alpha/beta Counter



Thermo FH40G-L10



Exploranium GR-130 Gamma Spec



Ludlum 9DP



Canadian
Light
Source

Centre canadien
de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

RADIOLOGICAL WORK

- Machining Radioactive Material
 - Very little demand
- High Radiation Area Work
 - Uncommon in CLS
 - Common in MIP
- Contractors in Radiological Control Areas
 - Very common
- HSE Department
 - Sealed source use
 - Radiation surveys

RADIOLOGICAL MONITORING

- Contamination Surveys
 - Performed routinely throughout facility
 - Beamline radioactive material experiments
- Accelerator Cooling Water Analysis
 - Performed routinely



TRAINING

- Radiation training requirements determined by type of work and access requirements
- Radiation Awareness Module - Basic level training for Users
- General Radiation Training – Non-NEW CLS staff and contractors
- Radiological Worker Training – NEW
- Worker/specialized Training (ACIS Lockup, Survey, Sealed Source Use, other)



Events

- **Magnet Event**
 - Upgrade to transfer line power supplies resulted in bend magnet polarity reversal
 - Radiation alarm of 82 $\mu\text{Sv/h}$ in RCA
 - No exposure to any worker
 - Improvements to work management resulted

- **Punctured Fe-55 source (3.43 MBq)**
 - Loss of 0.7 MBq determined
 - No dose
 - Improved handling procedures resulted

Medical Isotope Project (MIP)

Accelerator based production of Mo-99 from Mo-100.

- 35 MeV (40 kW) 3 section linear accelerator
- Production currently 20 kBq per week
- Clinical trials to start in fall of 2015
- Larger scale production facility planning underway

Mo-99 → Tc-99 for medical imaging



Canadian
Light
Source

Centre canadien
de rayonnement
synchrotron

TEN YEARS
OF DISCOVERY

Future Challenges

- Top-Up Operation
 - Planning started in 2012
 - Leadership + staffing changes delayed
 - Now not an ‘official priority’, but much interest
 - 2017?
- Staff Dosimetry
 - Dose results historically low
 - Re-evaluation of dosimetry requirements for CLS staff
2016





Thank you. Questions?